

Sewage, Dewatering

Waste-Mate

260 Series

Submersible sewage/*effluent or dewatering pump



Features and Benefits	Product Specifications	Technical Data	Literature and Documents
-----------------------	------------------------	----------------	--------------------------

HERTZ	60 Hz		
MOTOR	1/2 HP		
VOLTAGE	115 - 460 V		
PHASE	1 or 3 Ph		
RPM	1750 RPM		
TYPE	Split phase or 3 phase		
INSULATION	Class B		
AMPS	1.5 - 10.4 Amps		
OPERATION	Automatic or nonautomatic		
AUTO ON/ OFF POINTS	12" / 4" (30 cm / 10 cm)		
DISCHARGE SIZE	2" or 3" NPT		
SOLIDS HANDLING	2" (50 mm) spherical solids		
CORD LENGTH	10' (3 m) auto, 15' (5 m) nonauto standard		
CORD TYPE	UL listed, 3-wire neoprene cord and plug		
MAX HEAD	21.5' (6.6 m)		
MAX FLOW RATE	128 GPM (484 LPM)		
MAX OPERATING TEMP	130 °F (54 °C)		
COOLING	Oil filled		
MOTOR PROTECTION	Auto reset thermal overload (1 Ph)		
CAP	Cast iron		
MOTOR HOUSING	Cast iron		
PUMP HOUSING	Cast iron		
BASE	Cast iron or engineered plastic		
UPPER BEARING	Sleeve bearing		
LOWER BEARING	Sleeve bearing		
MECHANICAL SEALS	Carbon and ceramic		
IMPELLER TYPE	Non-clogging vortex		
IMPELLER	Engineered plastic with metal insert		
HARDWARE	Stainless steel		
MOTOR SHAFT	AISI 1215 cold rolled steel		
GASKET	Neoprene		

Specifications for the Zoeller M267 Waste Mate Sewage Ejector ½ Horsepower ejector pump 1.6.17